

Technical Bulletin #2009-04

To: All Grand-Am Competitors
 Effective: Immediately, unless otherwise noted.
 From: Grand-Am
 Date: February 27, 2009

(Changes in Red)

GENERAL AUTOMOBILE REGULATIONS

7-1.1 (Add) Mufflers are mandatory.

12-4.2 (Add) Fuel cells must contain fuel cell foam to a minimum of 80% of the enclosed volume.

15-1.7 (Add)

GT and KONI Challenge cars - A drivers side window net meeting SFI Specification 27.1 is required. (The rest of the section to remain as currently issued.)

15-1.10 (Add) The use of center and door side nets is required. Only Grand-Am approved mounting kits and SFI 37.1 Kevlar approved nets are allowed. The only approved release mechanisms are the Safety Solutions swing-close hasp and the Safecraft "bullet" release. The Safecraft release may be used in combination with the swing-close hasp.

DAYTONA PROTOTYPE REGULATIONS

(found at <http://www.grand-am.com/assets/2009engineist4.pdf>)

PONTIAC 5.0L V8

~~#12580420 intake manifold~~ PN 54042, LSRXT Intake Manifold, PN 54009-8 LS6-type port gasket replacement seal set.

PORSCHE GT3R Flat 6

Up to 3.99 liter displacement. ~~with unlimited components.~~ Maximum RPM: 9000. This engine must run a five speed transaxle.

7-4 Shock Absorbers

7-4.1 Approved brands and models.

~~OHLINS TT-44~~

GT REGULATIONS

2-17 Pontiac GTO, Grand Prix, G6 GXP.R or Grand Am,.

2-17.2 Minimum weight ~~2725 or 2834 with DP transaxle.~~ Maximum rear weight percentage is 50%.

KONI CHALLENGE REGULATIONS

8-3 Street Tuner (ST)

| Car | Final Dr | Fuel Cap | GAC Wt | Options |
|----------------------|----------|----------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Audi TT | | | 2850 | |
| BMW 328i (E90) | | | | front bumper extensions 51-19-0-404-056-057 |
| Mazda RX8 | | 18.5 | | |
| Porsche Boxster | | | | (986 body) eligibility extended for an additional 2 year period. |
| Subaru | | 18.5 | | |
| Volkswagen GTi | | | | Must use air inlet restrictor as supplied by Grand-Am. |
| Volkswagen Jetta GLi | 3.94:1 | 17.0 | 2750 | Tires size 225/45/17. Must run stock exhaust with muffler, stock air box with stock air filter, stock boost and stock RPM Unit. Must use OEM ECU. Maximum RPM 6800, Maximum boost 12.0 psi . Must use air inlet restrictor as supplied by Grand-Am. |